Focus Report

New Chemicals Program PMN Number: L-12-0012

Focus Date: 10/23/2011 11:00:00 PM Report Status: In Progress

Consolidated Set:

Focus Chair: Rose Allison Contractor: Stephen Wieroniey

I. Notice Information

Submitter: Tracerco CAS Number: 31599-61-8

Chemical Name: Benzene, 4-iodo-1,2-dimethyl-

Use: Tracer chemical used to monitor and measure the movement of oil in deep oil/gas bearing

geological strata. P2 Claim: The LVE substance is a substitute for radionuclide tracers to measure the flow rate in oil-bearing strata.

Other Uses:

PV-Max: 1,000 Kg/yr Binding Option: Yes Manufacture: Import: X

II. SAT Results

(1) Health Rating: 1-2 Eco Rating: 2 Comments:

Occupational: 1-2A Non-Occupational: Environmental: 2

(1) **PBT:** 1 1 **Comments:**

Awaiting Human Health Entry Awaiting Human Health Entry Awaiting Human Health Entry

III. OTHER FACTORS

Categories:

Health Chemical Category: Ecotox SAR and neutral organic chemicals;

TSCA New Chemical Category:

Related Cases/Regulatory History:

Health related Cases:

Ecotox Related Cases: Analogs: Regulatory History: -GRANTED

-PENDING A NON-5(e) SNUR/LTTR SENT

-FOCUS DROP

MSDS/Label Information:

MSDS: Yes Label: No

General Equipment: safety glasses / impervious gloves / protective work clothing / properly operating chemical fume

hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per

minute.

Respirator: suitable respirator when high concentrations are present

Health Effects: irritating to eyes, respiratory system, and skin

TLV/PEL (PMN or raw - None Established

material):

LVEPPE: impervious gloves / goggles / Tyvek suit

Exposure Based Information:

Exposure Based Review: N Exposure Based Review (Health): N Exposure Based Review (Eco): N Exposure Based (Occupational): No Exposure Based Review Exposure Based (Environmental):

IV. Summary of SAT Assessment

Fate:

Fate Summary: L-12-0012-13

FATE:

Liquid with MP < 25 C (E) log Kow = 4.25 (E) S = 17.6 mg/L at 25 C (E)

VP = 9.2E-2 torr at 25 C (NOMO5)

BP = 225-234 C (M) H = 1.94E-3 (E) log Koc = 2.79 (E) log Fish BCF = 2.47 (E) log Fish BAF = 2.49 (E)

POTW removal (%) = 63 via sorption and stripping Time for complete ultimate aerobic biodeg = wk

Sorption to soils/sediments = strong

Volatilization half-life from a standard river = 2 hrs Volatilization half-life from a standard lake = 6 da Atmospheric Oxidation Half-life = 29 hr via OH radical

PBT Potential: P1B1

*CEB FATE: Migration to ground water = slow

Health:

Health Summary:

Absorption is moderate all routes based on physical/chemical properties. There is concern for mutagenicity by analogy to 3-iodotoluene which is positive in a micronucleus assay. There is uncertain concern for oncogenicity because the benzene ring can be epoxidized. There is also uncertain concern for solvent-type neurotoxicity and concern for developmental toxicity by analogy to small benzenes. Low moderate concern.

Ecotox:

Ecotox Values:

Fish 96-h LC50: 1.9(P)
Daphnid 48-h LC50: 1.5(P)
Green algal 96-h EC50: 1.8(P)
Fish Chronic Value: 0.22(P)
Daphnid ChV: 0.24(P)
Algal ChV: 1.0(P)

Ecotox values comments: Predictions are based on SARs for neutral organic chemicals; SAR chemical class = iodinated

hydrocarbon; MW 232; log Kow = 4.25 (EPI); solid with mp = 41 C (M); pH7; effective concentrations based on 100% active ingredients and mean measured concentrations; hardness

<150.0 mg/L as CaCO3; and TOC <2.0 mg/L;

Ecotox Factors:

Assessment Factor: 10

Concern Concentration:

- Acute Value

Concern Concentration: 22

- Chronic Value

V. Summary of Exposures/Releases Engineering Summary: L-12-0012

Exposures/Releases	Release	Release	Release
Scenario	Processing: Tracer	Processing: Tracer	Processing: Tracer
	Chemical Formulation	Chemical Formulation	Chemical Formulation
Sites	1	1	1
Media	Water or Incineration or Landfill	Air	Air
Descriptor A	Conservative	Output 2	Typical
Quantity A (kg/site/day)	6.2E-1	7.6E-3	1.9E-4
Frequency A (day/year)	16	16	16
Descriptor B			Worst Case
Quantity B (kg/site/day)			1.9E-4
Frequency B (day/year)			16
From	Equipment Cleaning Losses of Liquids from a Single, Small Vessel	Equipment Cleaning Losses of Liquids from a Single, Small Vessel	Loading Liquid Product into Containers
Workers			
Exposure Type			

Engineering Summary:	Release	Release	Release
Exposures/Releases			
Scenario	Processing: Tracer Chemical Formulation	Processing: Tracer Chemical Formulation	Use: Injection of Tracer Chemical into Oil-Bearing Strata
Sites	1	1	1
Media	Air	Water or Incineration or Landfill	Air
Descriptor A	Typical	High End	Typical
Quantity A (kg/site/day)	1.8E-4	3.8E-1	6.2E-5
Frequency A (day/year)	16	16	50
Descriptor B	Worst Case		Worst Case
Quantity B (kg/site/day)	1.8E-4		6.2E-5
Frequency B (day/year)	16		50
From	Unloading Liquid Raw Material from Containers	Cleaning Liquid Residuals from Containers Used to Transport the Raw Material	Unloading Liquid Product from Containers
Workers			
Exposure Type			

V. Summary of Exposures/Releases Engineering Summary: L-12-0012

Exposures/Releases	Release	Release	Exposure
Scenario	Use: Injection of Tracer Chemical into Oil-Bearing Strata	Use: Injection of Tracer Chemical into Oil-Bearing Strata	Processing: Tracer Chemical Formulation
Sites	1	1	1
Media	Water or Incineration or Landfill	Incineration	Dermal
Descriptor A	High End	Output 2	High End
Quantity A (kg/site/day)	1.2E-1	2.0E+1	7.1E+2
Frequency A (day/year)	50	50	16
Descriptor B			
Quantity B (kg/site/day)			
Frequency B (day/year)			
From	Cleaning Liquid Residuals from Containers Used to Transport the Product	Oil Production	Loading Liquid Product into Containers
Workers			3
Exposure Type			Liquid

Engineering Summary:	Exposure	Exposure	Exposure
Exposures/Releases			
Scenario	Processing: Tracer	Processing: Tracer	Processing: Tracer
	Chemical Formulation	Chemical Formulation	Chemical Formulation
Sites	1	1	1
Media	Inhalation	Dermal	Inhalation
Descriptor A	Worst Case	High End	Worst Case
Quantity A (kg/site/day)	9.3E-1	1.7E+3	8.5E-1
Frequency A (day/year)	16	16	16
Descriptor B	Typical		Typical
Quantity B (kg/site/day)	3.1E-2		2.8E-2
Frequency B (day/year)	16		16
From	Loading Liquid Product into	Unloading Liquid Raw	Unloading Liquid Raw
	Containers	Material from Containers	Material from Containers
Workers	3	3	3
Exposure Type	Vapor	Liquid	Vapor

V. Summary of Exposures/Releases Engineering Summary: L-12-0012

Exposures/Releases	Exposure	Exposure	
Scenario	Use: Injection of Tracer Chemical into Oil-Bearing Strata	Use: Injection of Tracer Chemical into Oil-Bearing Strata	
Sites	1	1	
Media	Dermal	Inhalation	
Descriptor A	High End	Worst Case	
Quantity A (kg/site/day)	7.1E+2	8.9E-1	
Frequency A (day/year)	50	50	
Descriptor B		Typical	
Quantity B (kg/site/day)		3.0E-2	
Frequency B (day/year)		50	
From	Unloading Liquid Product from Containers	Unloading Liquid Product from Containers	
Workers			
Exposure Type	Liquid	Vapor	

VI. Focus Decision and Rationale

Regulatory Actions

Regulatory Decision: LVE Conditional Grant Decision Date: 10/23/2011

Type of Decision:

Rationale: L-12-0012 was given a conditional grant. Human health concerns were

low-moderate for dermal, drinking water and inhalation exposure. Potential risks to workers were addressed by adequate dermal PPE. However, the submitter must amend the notice and MSDS to include a NIOSH-certified organic vapor cartridge respirator. Ecotoxicity concerns were high. Potential risks to the environment were low due to less than 20 days of exceedance of

the COC. This LVE was bound at 1,000 kg/year.

COC: Chronic – 3 ppb, Acute – 40 ppb.

Summary of Exposures and Releases:

Processing:

1 site, 16 days/year, 3 workers

Inhalation 1: Vapor: Typical: 3.1E-2 mg/day over; Worst Case: 9.3E-1 mg/day Inhalation 2: Vapor: Typical: 2.8E-2 mg/day; Worst Case: 8.5E-1 mg/day over

Dermal 1: 7.1E+2 mg/day (Liquid 40%) Dermal 2: 1.7E+3 mg/day (Liquid 98%)

Releases to Water 1: 6.2E-1 kg/site-day over 16 days/yr

Or Incineration or Landfill

Releases to Water 2: 3.8E-1 kg/site-day over 16 days/yr

Or Incineration or Landfill

Releases to Air 1: 7.6E-3 kg/site-day over 16 days/yr

Releases to Air 2: Typical: 1.9E-4 kg/site-day over 16 days/yr; Worst Case:

1.9E-4 kg/site-day over 16 days/yr

Releases to Air 3: Typical: 1.8E-4 kg/site-day over 16 days/yr; Worst Case:

1.8E-4 kg/site-day over 16 days/yr

Fate Releases to Water (63% Removal):

SWC: 6.84E+01 ppb

DW: LADD: 2.50E-06 mg/kg/day; ADR: 3.30E-03 mg/kg/day

Use:

1 site, 50 days/year, 3 workers

Inhalation: Vapor: Typical: 3.0E-2 mg/day over 50 days/yr; Worst Case:

8.9E-1 mg/day

Dermal: 7.1E+2 mg/day (Liquid 40%)

Releases to Water: 1.2E-1 kg/site-day over 50 days/yr

Or Incineration or Landfill

Releases to Air: Typical: 6.2E-5 kg/site-day over 50 days/yr; Worst Case:

6.2E-5 kg/site-day over 50 days/yr

Fate Releases to Water (63% Removal):

SWC: 4.19E+01 ppb

DW: LADD: 4.27E-06 mg/kg/day; ADR: 1.91E-03 mg/kg/day

>COC (22 ppb): 8/50 release days

P2 Rec Comments:

Testing:

Final Recommended:

Health:

Eco: Fate:

Other:

06/02/2015 03:22:17 PM

SAT Report

PMN Number: L-12-0012 SAT Date: 10/18/2011 Print Date: 6/2/2015

Related cases:

Health related cases:

Ecotox related cases: Analogs:

Concern levels:

Type of Concern: <u>Health</u> <u>Eco</u> <u>Comments</u>

Level of Concern: 1-2 2

Persistence
1 1 1 1 1 Awaiting
Human Health
Entry

Exposure Based Review:

Health: No **Ecotox:** No

Routes of exposure: Health: Dermal Drinking Water Inhalation

Ecotox: All releases to water

Fate: ;

Keywords:

Keywords:

Summary of Assessment:

Fate:

Fate Summary: L-12-0012-13

FATE:

Liquid with MP < 25 C (E)

 $\log Kow = 4.25 (E)$

S = 17.6 mg/L at 25 C (E)

VP = 9.2E-2 torr at 25 C (NOMO5)

BP = 225-234 C (M)

H = 1.94E-3 (E)

 $\log Koc = 2.79 (E)$

 $\log \text{ Fish BCF} = 2.47 (E)$

log Fish BAF = 2.49 (E)

POTW removal (%) = 63 via sorption and stripping

Time for complete ultimate aerobic biodeg = wk

Sorption to soils/sediments = strong

Volatilization half-life from a standard river = 2 hrs

Volatilization half-life from a standard lake = 6 da

Atmospheric Oxidation Half-life = 29 hr via OH radical

PBT Potential: P1B1

*CEB FATE: Migration to ground water = slow

Health:

Health Summary: Absorption is moderate all routes based on physical/chemical properties. There is concern for mutagenicity by analogy to 3-iodotoluene which is positive in a micronucleus assay. There is uncertain concern for oncogenicity because the benzene ring can be epoxidized. There is also uncertain concern for solvent-type neurotoxicity and concern for developmental toxicity by analogy to small benzenes. Low moderate concern.

Ecotox:

Test	Test	Test End	Predicted	Measured	Comments
Organism	Type	Point	11001000	112000000	0 022220
fish	96-h	LC50	1.9		
daphnid	48-h	LC50	1.5		
green algal	96-h	EC50	1.8		
fish	_	chronic	0.22		
		value			
daphnid	_	chronic	0.24		
		value			
algal	_	chronic	1.0		
		value			
Sewage	3-h	EC50	_		
Sludge					
Sewage	_	Chronic	_		
Sludge		Value			

Ecotox Values Comments: Predictions are based on SARs for neutral organic chemicals; SAR chemical class = iodinated hydrocarbon; MW 232; log Kow = 4.25 (EPI); solid with mp = 41 C (M); pH7; effective concentrations based on 100% active ingredients and mean measured concentrations; hardness <150.0 mg/L as CaCO3; and TOC <2.0 mg/L;

Factors	Values	Comments
Assessment Factor	10	
Concentration of Concern		
(ppb)		
Acute		
Concentration of Concern	22	
(ppb) Chronic		
SARs	neutral organic chemicals	
SAR Class	iodinated hydrocarbon	new chemicals category: neutral
		organics
TSCA New Chemcial		
Category		

Ecotox Factors Comments:

SAT Chair: Becky Jones

Fate assessor: Ecotox assessor: Health assessor: